




Swiss precision for excellent audio quality

VOICE TECHNOLOGIES



VT860MKII Cardioid Headset Combination

As flexible as your work.

With the VT860MKII headworn (with a cardioid capsule) Voice Technologies presents an excellent solution for TV, 2-way radio applications, public speaking and broadcast studio operations. It has been developed for outstanding clarity in noisy environments.

Much consideration has been put into the physical design of the VT860MKII. The flexible gooseneck enables the user to position the microphone for optimum sound and gain before feedback.

A one size fits all soft earpiece is connected to the integrated VT600 earphone. The headband is highly resistant to corrosion and is easy to clean.

Application area: Broadcast - Video - Presentations



Audio Bauer Pro AG, Bernerstrasse-Nord 182, CH-8064 Zürich, Switzerland
Phone: +41 44 432 32 30, Fax: +41 44 432 65 58, Email: info@vt-switzerland.com

www.vt-switzerland.com

VT860MKII Cardioid Headset Combination

Specifications:

Microphone:

Generating Element:	Electret Condenser
Polar Pattern:	Cardioid
Frequency Range:	50—18 kHz
Sensitivity(@1kHz):	-53dB \pm 3dB 1V/microbar (2.2mV/Pa)
Noise Level:	32dB "A" weighted
Max. Input SPL:	120 dB based on 9V supply
Impedance:	2.8 to 6.8 kOhms, nominal 4.4 kOhms
Bias/+VDC:	1.5V to 9V
Dynamic Range:	88db
Signal Noise Ratio:	62dB @94dB SPL
Color:	beige
Cable:	Length 1.5m \varnothing 2mm
Weight:	49g

Wiring Configuration (3-wire)

Red	"+"
Shield	Ground
White	Signal


Earphone:

Element:	Subminiature Magnetic Receiver
Frequency Range:	200Hz-8kHz
Impedance:	500 kOhm
Sensitivity:	104+/-3dB
Distortion:	5% max.

Wiring Configuration (2-wire) :

Red	"+"
Green	"-"

Frequency range:



Standard Accessories



Strap



Ear/Beige



WS800

Audio Bauer Pro AG, Bernerstrasse-Nord 182, CH-8064 Zürich, Switzerland
Phone: +41 44 432 32 30, Fax: +41 44 432 65 58, Email: info@vt-switzerland.com

www.vt-switzerland.com